



PF51 DUAL DRIVE CONTROL PANEL

RoHS Certified, CE Marked

► Features & Benefits

- » **IP66 Protected** enclosure with cord strain reliefs
- » **Dual 200 watt controllers** for brushless DC geatmotors
- » **230 volt, single phase 50 or 60 Hz power input, 10 amp Max**
- » **Includes internal circuit breaker** compatible with GFCI
- » **M12, 4 pole female, receptacle connection to emergency stop circuit with illuminated button (supplied by KES)**
- » **Relays to halt conveyor when emergency stop is pressed or guard is removed from either conveyor, condition indicated by LED lights on the relays**
- » **Dual 3 position start/stop/reset switch for each conveyor**
- » **Speeds are preset** to 1800 rpm (Conveyor 1) and 1800 rpm (Conveyor 2)
- » **1.9m cable for Conveyor 1/PRP** outside enclosure with bare leads for the KES's Harting connector
- » **1.5m cable for Conveyor 2/ECU** outside enclosure with 3 modular connectors
- » Intended for use in kit with additional cabling



► Part Number

P	F	5	1	-	E	P	A	N	E	L	-	E	U	N	-	2	3	0	-	1
Model Specification Number					Application Identifier				Voltage			Phase								

► Drawing

